

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity 18696 Brown

Alternate Names 18696 Brown

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Sprinter Marking Inc
1805 Chandlersville Road
Zanesville, Ohio 43701 USA

Emergency

24 hour Emergency Telephone No. ChemTel 1-800-255-3924 (MIS0006470)
International +01-813-248-0585

Customer Service: Sprinter Marking, Inc Phone +1 (740) 453-1000
Fax +1 (740) 453-6750
Email: sales@sprintermarking.com

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor.

Eye Dam. 2A;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

2.2. Label elements



Danger

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P233 Keep container tightly closed.

P240 Ground, bond container and receiving equipment.

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapors, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice or attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction. P.O. Box 13859

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1-Methoxy-2-propanol CAS Number: 0000107-98-2	50 - 75	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Isopropyl Alcohol CAS Number: 0000067-63-0	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	5 - 10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
ETHYL ACETATE, EAC CAS Number: 0000141-78-6	5 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Rosin, Fumeric CAS Number: 800680-57-9	5 - 10	Not Classified	[1]
Ethanol CAS Number: 0000064-17-5	5 - 10	Flam. Liq. 2;H225	[1][2]
Acetic acid, 1-methylethyl ester CAS Number: 0000108-21-4	1 - 5	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Carbon black CAS Number: 0001333-86-4	1 - 5	Not Classified	[1][2]

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Cellulose Nitrate CAS Number: 0009004-70-0	1 - 5	Flam. Sol. 1;H228	[1]
---	-------	-------------------	-----

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Move the exposed person to fresh air at once. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if any discomfort continues.
Eyes	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Use foam, extinguishing powder, dry chemicals, or carbon dioxide. Water may be ineffective. Water may be used to keep fire exposed containers cool.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: None

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

***Sprinter Marking* Safety Data Sheet**

18696 Brown

SDS Revision Date: 03/01/2024

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust, fume, gas, mist, vapors, spray.

5.3. Advice for fire-fighters

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

ERG Guide No. 129

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid sparks, flames, heat and smoking. Ventilate. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spill: Use a non-combustible material like vermiculite, sand or earth to soak up product and place in a container for later disposal.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Keep in containers lightly closed in a cool, well ventilated place. Do not store with oxidizing agents or acids. Keep in the original container. Avoid direct sunlight

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool dry area, away from heat, sparks and open flame.

Keep containers sealed when not in use.

Store out of direct sunlight.

Store in a cool dry place.

Incompatible materials: Store away from oxidizers and acids.

See section 2 for further details. - [Storage]:

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

7.3. Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0000064-17-5	Ethanol	OSHA	TWA 1000 ppm (1900 mg/m3)
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1900 mg/m3)
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m3) STEL 500 ppm
		ACGIH	TWA: 200 ppm STEL: 400 ppm
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
0000107-98-2	1-Methoxy-2-propanol	OSHA	No Established Limit
		ACGIH	100 ppm STEL
		NIOSH	TWA 100 ppm (360 mg/m3) ST 150 ppm (540 mg/m3)
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	TWA 250 ppm (950 mg/m3)
		ACGIH	TWA: 100 ppm STEL: 200 ppm
		NIOSH	no established RELs
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m3)
		ACGIH	TWA: 150 ppm, STEL 200 ppm
		NIOSH	TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3)
0000141-78-6	ETHYL ACETATE, EAC	OSHA	TWA 400 ppm (1400 mg/m3)
		ACGIH	TWA: 150 ppm
		NIOSH	TWA 400 ppm (1400 mg/m3)
0001333-86-4	Carbon black	OSHA	TWA 3.5 mg/m3
		ACGIH	TWA: 3 mg/m3
		NIOSH	TWA 3.5 mg/m3 Ca TWA 0.1 mg PAHs/m3 [in presence of polycyclic aromatic hydrocarbons (PAHs)]
0009004-70-0	Cellulose Nitrate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
800680-57-9	Rosin, Fumeric	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

8.2. Exposure controls

Respiratory

Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. The following should be effective types of air purifying respirators: Organic vapor cartridge.

Eyes

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene/ethyl vinyl alcohol laminate ("PE/EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Do not smoke, or drink in work area. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Colored Liquid
Odor	Sweet alcohol
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	82 C 160 F
Flash Point	10-15 C 50-60 F method (setaflash)
Evaporation rate (Ether = 1)	1.0
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 3.0 Upper Explosive Limit: 19.0
Vapor pressure (Pa)	4.16kPa temperature (C) 20
Vapor Density	>2
Relative Density	0.810 g/ml temperature (C) 20
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	65-75 wt-% Approximately 5.9 Lbs /gal
% Volatile	65-75%

9.2. Other information

No other relevant information.

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

High temperatures and fires.

10.5. Incompatible materials

Store away from oxidizers and acids.

10.6. Hazardous decomposition products

None

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1-Methoxy-2-propanol - (107-98-2)	4,277.00, Rat - Category: NA	> 2,000.00, Rat - Category: 4	No data available	No data available	No data available
Isopropyl Alcohol - (67-63-0)	5,840.00, Rat - Category: NA	12,800.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available
ETHYL ACETATE EAC - (141-78-6)	4,934.00, Rat - Category: 5	20,001.00, Rabbit - Category: NA	58.60, Rat - Category: NA	No data available	No data available
Rosin, Fumeric - (800680-57-9)	No data available	No data available	No data available	No data available	No data available
Ethanol - (64-17-5)	10,470.00, Rat - Category: NA	17,100.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Acetic acid, 1-methylethyl ester - (108-21-4)	6,750.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	17,129.60, Rabbit - Category: NA	No data available	No data available
Carbon black - (1333-86-4)	10,001.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Cellulose Nitrate - (9004-70-0)	5,000.00, Mouse - Category: 5	No data available	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000064-17-5	Ethanol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A3
0000067-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	A4
0000107-98-2	1-Methoxy-2-propanol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000141-78-6	ETHYL ACETATE, EAC	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0001333-86-4	Carbon black	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
		ACGIH	A3
0009004-70-0	Cellulose Nitrate	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
800680-57-9	Rosin, Fumeric	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1-Methoxy-2-propanol - (107-98-2)	6,812.00, Leuciscus idus	> 4,600.00, Daphnia magna	> 1,000.00 (96 hr), Pseudokirchneriella subcapitata
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	Not Available	Not Available
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.00 (72 hr), Pseudokirchnerella subcapitata
ETHYL ACETATE EAC - (141-78-6)	230.00, Pimephales promelas	100.00, Daphnia magna	101.00 (72 hr), Desmodesmus subspicatus
Rosin, Fumeric - (800680-57-9)	Not Available	Not Available	Not Available
Ethanol - (64-17-5)	15,400.00, Lepomis macrochirus	10,001.00, Daphnia magna	17.921 (96 hr), Ulva pertusa
Acetic acid, 1-methylethyl ester - (108-21-4)	Not Available	Not Available	Not Available
Carbon black - (1333-86-4)	1,000.00, Danio rerio	Not Available	10,001.00 (72 hr), Desmodesmus subspicatus
Cellulose Nitrate - (9004-70-0)	Not Available	Not Available	579.00 (96 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

Sprinter Marking Safety Data Sheet

18696 Brown

SDS Revision Date: 03/01/2024

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1210	UN1210	UN1210
14.2. UN proper shipping name	Printing ink	Printing ink	Printing ink
14.3. Transport hazard class(es)	DOT Hazard Class: 3 DOT Label: 3	IMDG: 3 Sub Class: Not Applicable EmS: F-E, S-D	Air Class: 3 Packing Instruction: Cargo Only - 364, Passenger -353
14.4. Packing group	II	II	II
14.5. Environmental hazards			

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Section 15. Regulatory information


Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All components of this material are either listed or exempt from listing on the TSCA Inventory.

Sprinter Marking Safety Data Sheet 18696 Brown

SDS Revision Date: 03/01/2024

NFPA Rankings:



US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

Note: Ethanol (Ethyl alcohol) has been placed on the California Proposition 65 Cancer and Developmental Lists when in alcoholic beverages.

EPCRA 311/312 Chemicals and RQs (lbs):

N-Butyl Acetate (5,000.00)

ETHYL ACETATE, EAC (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethanol

Isopropyl Alcohol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

1-Methoxy-2-propanol

Acetic acid, 1-methylethyl ester

N-Butyl Acetate

Carbon black

Cellulose Nitrate

Ethanol

ETHYL ACETATE, EAC

Isopropyl Alcohol

Pennsylvania RTK Substances (>1%):

1-Methoxy-2-propanol

***Sprinter Marking* Safety Data Sheet**

18696 Brown

SDS Revision Date: 03/01/2024

Acetic acid, 1-methylethyl ester

N-Butyl Acetate

Carbon black

Cellulose Nitrate

Ethanol

ETHYL ACETATE, EAC

Isopropyl Alcohol

Section 16. Other information

SDS Revision Date 03/01/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This product is RoHS and REACH compliant. It does not contain any of the RoHS listed substances. It does not contain any chemical from the candidate list of Substances of Very High Concern (SVHC), Annex XIV, or Annex XVII of Reach.

This information is based on our present knowledge. However, it does not constitute a guarantee for any specific product properties.

Sprinter Marking urges the recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. The use of this product is beyond the control of Sprinter Marking or its distributor, therefore, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.

End of Document