

# *Sprinter Marking, Inc* Safety Data Sheet

## 18114 UV Marking Ink

SDS Revision Date: 03/03/2016

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity** 18114 UV Marking Ink  
**Alternate Names** 18114 UV Marking Ink

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** See Technical Data Sheet.  
**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** Sprinter Marking, Inc  
1805 Chandlersville Road  
Zanesville, Ohio 43701 USA

#### Emergency

**24 hour Emergency Telephone No.** ChemTel 1-800-255-3924 (MIS0006470)  
International +01-813-248-0585

**Customer Service: Sprinter Marking, Inc** Phone +1.740.453.1000  
Fax +1.740.453.6750  
Email: sales@sprintermarking.com

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
STOT SE 3;H336 May cause drowsiness or dizziness.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Warning**

H226 Flammable liquid and vapor.

# Sprinter Marking, Inc Safety Data Sheet

## 18114 UV Marking Ink

SDS Revision Date: 03/03/2016

### [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P280 Wear protective gloves / eye protection / face protection.

### [Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
<b>1-Methoxy-2-propanol</b> CAS Number: 0000107-98-2	75 - 100	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
<b>Rosin, Fumaric, Maleic Adduct</b> CAS Number: 0068201-59-2	1.0 - 10		[1]
<b>Isopropyl Alcohol</b> CAS Number: 0000067-63-0	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Remove and isolate contaminated clothing and shoes.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Wash skin with soap and water.

In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.

# ***Sprinter Marking, Inc* Safety Data Sheet**

## **18114 UV Marking Ink**

**SDS Revision Date: 03/03/2016**

Keep victim warm and quiet.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

### **Inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

### **Eyes**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### **Skin**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

### **Ingestion**

DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

## **4.2. Most important symptoms and effects, both acute and delayed**

### **Overview**

Effects of contact or inhalation may be delayed. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

### **Inhalation**

May cause drowsiness or dizziness.

## **5. Fire-fighting measures**

### **5.1. Extinguishing media**

Use foam, extinguishing powder, dry chemicals, or carbon dioxide. Water may be ineffective. Water may be used to keep fire exposed containers cool.

### **5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

### **5.3. Advice for fire-fighters**

Wear positive pressure self-contained breathing apparatus (SCBA).

Structural firefighters' protective clothing will only provide limited protection.

**HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

# **Sprinter Marking, Inc Safety Data Sheet**

## **18114 UV Marking Ink**

**SDS Revision Date: 03/03/2016**

Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Containers may explode when heated.

Many liquids are lighter than water.

May cause toxic effects if inhaled or absorbed through skin.

Inhalation or contact with material may irritate or burn skin and eyes.

Fire will produce irritating, corrosive and/or toxic gases.

Vapors may cause dizziness or suffocation.

Runoff from fire control or dilution water may cause pollution.

**ERG Guide No.** 129

### **6. Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

#### **6.2. Environmental precautions**

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### **6.3. Methods and material for containment and cleaning up**

**Large Spill:** As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away.

Stay upwind. Keep out of low areas.

Ventilate closed spaces before entering.

**Small Spill:** Use a non-combustible material like vermiculite, sand or earth to soak up product and place in a container for later disposal.

### **7. Handling and storage**

#### **7.1. Precautions for safe handling**

Keep in the original container.

The requirements of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations apply if the flashpoint is between 21°C and 32°C.

See section 2 for further details. - [Prevention]:

#### **7.2. Conditions for safe storage, including any incompatibilities**

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Store in a cool dry place.

Incompatible materials: Store away from oxidizers and acids.

See section 2 for further details. - [Storage]:

#### **7.3. Specific end use(s)**

No data available.

# Sprinter Marking, Inc Safety Data Sheet

## 18114 UV Marking Ink

SDS Revision Date: 03/03/2016

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m3)STEL 500 ppm
		ACGIH	TWA: 200 ppmSTEL: 400 ppm Revised 2003,
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
		Supplier	No Established Limit
0000107-98-2	1-Methoxy-2-propanol	OSHA	No Established Limit
		ACGIH	TWA: 50 ppmSTEL: 75 ppm
		NIOSH	TWA 100 ppm (360 mg/m3) ST 150 ppm (540 mg/m3)
		Supplier	No Established Limit
0068201-59-2	Rosin, Fumaric, Maleic Adduct	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

##### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000107-98-2	1-Methoxy-2-propanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068201-59-2	Rosin, Fumaric, Maleic Adduct	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

#### 8.2. Exposure controls

##### Respiratory

Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. The following should be effective types of air purifying respirators: Organic vapor cartridge.

##### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

##### Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene/ethyl vinyl alcohol laminate ("PE/EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton

# Sprinter Marking, Inc Safety Data Sheet

## 18114 UV Marking Ink

SDS Revision Date: 03/03/2016

<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
<b>Other Work Practices</b>	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Colored Liquid
<b>Odor</b>	Sweet alcohol
<b>Odor threshold</b>	Not Measured
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	117C 243F
<b>Flash Point</b>	29-32C 85-90F
<b>Evaporation rate (Ether = 1)</b>	0.7(BU.AC=1)
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 3.0 <b>Upper Explosive Limit:</b> 19.0
<b>Vapor pressure (Pa)</b>	11(mm Hg)
<b>Vapor Density</b>	>2(air=1)
<b>Specific Gravity</b>	0.95G/ML@20C
<b>Solubility in Water</b>	85-90%
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC %</b>	85wt%

#### 9.2. Other information

No other relevant information.

# Sprinter Marking, Inc Safety Data Sheet

## 18114 Marking Ink

SDS Revision Date: 03/03/2016

### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

High temperatures, fires, and incompatibles.

#### 10.5. Incompatible materials

Store away from oxidizers and acids.

#### 10.6. Hazardous decomposition products

No hazardous decomposition data available.

### 11. Toxicological information

#### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
1-Methoxy-2-propanol - (107-98-2)	5,000.00, Rat - Category: 5	13,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Rosin, Fumaric, Maleic Adduct - (68201-59-2)	No data available	No data available	No data available	No data available	No data available
Isopropyl Alcohol - (67-63-0)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

**Sprinter Marking, Inc Safety Data Sheet**

**18114 UV Marking Ink**

SDS Revision Date: 03/03/2016

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

**12. Ecological information**

**12.1. Toxicity**

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1-Methoxy-2-propanol - (107-98-2) 1,000.00, Oncorhynchus	mykiss	500.00, Daphnia magna	1,000.00 (96 hr), Selenastrum capricornutum
Rosin, Fumaric, Maleic Adduct - (68201-59-2)	Not Available	Not Available	Not Available
Isopropyl Alcohol - (67-63-0) 1,400.00, Lepomis	macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus

**12.2. Persistence and degradability**

There is no data available on the preparation itself.

**12.3. Bioaccumulative potential**

Not Measured

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

This product contains no PBT/vPvB chemicals.

**12.6. Other adverse effects**

No data available.



# Sprinter Marking, Inc Safety Data Sheet

## 18114 UV Marking Ink

SDS Revision Date: 03/03/2016

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

### 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1210	UN1210	UN1210
<b>14.2. UN proper shipping name</b>	Printing ink	Printing ink	Printing ink
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> 3 <b>DOT Label:</b> 3	<b>IMDG:</b> 3 <b>Sub Class:</b> Not Applicable <b>EmS:</b> F-E, S-D	<b>Air Class:</b> 3 Packing Instruction: Cargo Only - 364, Passenger -353
<b>14.4. Packing group</b>	II	II	II
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>	No further information		
<b>14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not Applicable		

### 15. Regulatory information

#### Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

#### NFPA Rankings:



**Sprinter Marking, Inc Safety Data Sheet**

**18114 UV Marking Ink**

SDS Revision Date: 03/03/2016

WHMIS Classification B2



US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): No

**EPCRA 311/312 Chemicals and RQs:**

(No Product Ingredients Listed)

**EPCRA 302 Extremely Hazardous :**

(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals:**

Isopropyl Alcohol

**Proposition 65 - Carcinogens (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**N.J. RTK Substances (>1%):**

1-Methoxy-2-propanol

Isopropyl Alcohol

**Penn RTK Substances (>1%):**

1-Methoxy-2-propanol

Isopropyl Alcohol

**16. Other information**

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

***Sprinter Marking, Inc* Safety Data Sheet**

**18114 UV Marking Ink**

**SDS Revision Date: 03/03/2016**

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

This product is RoHS and REACH compliant. It does not contain any of the RoHS listed substances. It does not contain any chemical from the candidate list of Substances of Very High Concern (SVHC), Annex XIV, or Annex XVII of Reach.

This information is based on our present knowledge. However, it does not constitute a guarantee for any specific product properties.

Sprinter Marking urges the recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. The use of this product is beyond the control of Sprinter Marking or its distributor, therefore, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.

End of Document