

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity 18504 Fluorescent Yellow Marking Fluid
Alternate Names 18504 Fluorescent Yellow Marking Ink

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Sprinter Marking, Inc
1805 Chandlersville Road
Zanesville, Ohio 43701 USA

Emergency

24 hour Emergency Telephone No. ChemTel 1-800-255-3924 (MIS0006470)
International +01-813-248-0585

Customer Service: Sprinter Marking, Inc Phone +1.740.453.1000
Fax +1.740.453.6750
Email: sales@sprintermarking.com

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor.
Eye Irrit. 2;H319 Causes serious eye irritation.
STOT SE 3;H336 May cause drowsiness or dizziness.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|--|--------|
| N-Butyl Acetate CAS Number: 0000123-86-4 | 100 | Flam. Liq. 3;H226 STOT SE 3;H336 | [1][2] |
| Ethyl acetate CAS Number: 0000141-78-6 | 100 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | [1][2] |
| 1-Methoxy-2-propanol CAS Number: 0000107-98-2 | 25 - 50 | Flam. Liq. 3;H226 STOT SE 3;H336 | [1][2] |
| Isopropyl Alcohol CAS Number: 0000067-63-0 | 25 - 50 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | [1][2] |
| Titanium dioxide CAS Number: 0013463-67-7 | 10 - 25 | | [1][2] |
| Rosin, Fumeric CAS Number: 800680-57-9 | 1.0 - 10 | | [1] |
| Ethanol CAS Number: 0000064-17-5 | 1.0 - 10 | Flam. Liq. 2;H225 | [1][2] |
| Acetic acid, 1-methylethyl ester CAS Number: 0000108-21-4 | 1.0 - 10 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | [1][2] |

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

| | | | |
|---|----------|----------------|-----|
| Cellulose Nitrate CAS Number: 0009004-70-0 | 1.0 - 10 | Expl. 1.1;H201 | [1] |
|---|----------|----------------|-----|

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Move the exposed person to fresh air at once. If not breathing, give artificial respiration. Give oxygen. Get medical attention if any discomfort continues

Eyes

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Ingestion: May cause stomach pain or vomiting. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation

May cause drowsiness or dizziness.

Eyes

Causes serious eye irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Use foam, extinguishing powder, dry chemicals, or carbon dioxide. Water may be ineffective. Water may be used to keep fire exposed containers cool.

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

5.3. Advice for fire-fighters

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

ERG Guide No. 129

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid sparks, flames, heat and smoking. Ventilate. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spill: Use a non-combustible material like vermiculite, sand or earth to soak up product and place in a container for later disposal.

7. Handling and storage

7.1. Precautions for safe handling

Keep in containers lightly closed in a cool, well ventilated place. Do not store with oxidizing agents or acids. Keep in the original container. Avoid direct sunlight

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in a cool dry area, away from heat, sparks and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

Store in a cool dry place.

Incompatible materials: Store away from oxidizers and acids.

See section 2 for further details. - [Storage]:

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|----------------------------------|----------|---|
| 0000064-17-5 | Ethanol | OSHA | TWA 1000 ppm (1900 mg/m3) |
| | | ACGIH | STEL: 1000 ppm Revised 2009, |
| | | NIOSH | TWA 1000 ppm (1900 mg/m3) |
| | | Supplier | No Established Limit |
| 0000067-63-0 | Isopropyl Alcohol | OSHA | TWA 400 ppm (980 mg/m3)STEL 500 ppm |
| | | ACGIH | TWA: 200 ppmSTEL: 400 ppm Revised 2003, |
| | | NIOSH | TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3) |
| | | Supplier | No Established Limit |
| 0000107-98-2 | 1-Methoxy-2-propanol | OSHA | No Established Limit |
| | | ACGIH | TWA: 50 ppmSTEL: 75 ppm |
| | | NIOSH | TWA 100 ppm (360 mg/m3) ST 150 ppm (540 mg/m3) |
| | | Supplier | No Established Limit |
| 0000108-21-4 | Acetic acid, 1-methylethyl ester | OSHA | TWA 250 ppm (950 mg/m3) |
| | | ACGIH | TWA: 100 ppmSTEL: 200 ppm Revised 2003, |
| | | NIOSH | no established RELs |
| | | Supplier | No Established Limit |
| 0000123-86-4 | N-Butyl Acetate | OSHA | TWA 150 ppm (710 mg/m3) |
| | | ACGIH | TWA: 20 ppmS |
| | | NIOSH | TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3) |
| | | Supplier | No Established Limit |
| 0000141-78-6 | Ethyl acetate | OSHA | TWA 400 ppm (1400 mg/m3) |
| | | ACGIH | TWA: 150 ppm |
| | | NIOSH | TWA 400 ppm (1400 mg/m3) |
| | | Supplier | No Established Limit |
| 0009004-70-0 | Cellulose Nitrate | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0013463-67-7 | Titanium dioxide | OSHA | TWA 15 mg/m3 |
| | | ACGIH | TWA: 10 mg/m32B, Revised 2006, |
| | | NIOSH | Ca |
| | | Supplier | No Established Limit |

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

| | | | |
|-------------|----------------|----------|----------------------|
| 800680-57-9 | Rosin, Fumeric | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|----------------------------------|--------|---|
| 0000064-17-5 | Ethanol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000067-63-0 | Isopropyl Alcohol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0000107-98-2 | 1-Methoxy-2-propanol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-21-4 | Acetic acid, 1-methylethyl ester | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000123-86-4 | N-Butyl Acetate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000141-78-6 | Ethyl acetate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0009004-70-0 | Cellulose Nitrate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 800680-57-9 | Rosin, Fumeric | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

Respiratory

Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. The following should be effective types of air purifying respirators: Organic vapor cartridge.

Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

Sprinter Marking, Inc Safety Data Sheet

18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

| | |
|-----------------------------|--|
| Skin | Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene/ethyl vinyl alcohol laminate ("PE/EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton |
| Engineering Controls | Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn. |
| Other Work Practices | Do not smoke, or drink in work area. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. |

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

| | |
|--|---|
| Appearance | Colored Liquid |
| Odor | Sweet alcohol |
| Odor threshold | Not Measured |
| pH | Not Measured |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 82 C 160F |
| Flash Point | 10-15C 50-60F Method (Setaflash) |
| Evaporation rate (Ether = 1) | 1.0 |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 3.0 Upper Explosive Limit: 19.0 |
| Vapor pressure (Pa) | 4.16 kPa Temperature (C) 20 |
| Vapor Density | >2 |
| Specific Gravity | 0.810 g/mL Temperature |
| Solubility in Water | 65-75% |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | Not Measured |
| VOC % | 65-75% Approximately 5.9 Lbs/gal |
| % Volatile | 65-75% |

9.2. Other information

No other relevant information.

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

High temperatures, fires, and incompatibles.

10.5. Incompatible materials

Store away from oxidizers and acids.

10.6. Hazardous decomposition products

No hazardous decomposition data available.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr | Inhalation Gas LD50, ppm |
|-----------------------------------|-------------------------------|----------------------------------|---------------------------------|-------------------------------------|--------------------------|
| N-Butyl Acetate - (123-86-4) | 10,700.00, Rat - Category: NA | 17,600.00, Rabbit - Category: NA | No data available | No data available | No data available |
| Ethyl acetate - (141-78-6) | 5,600.00, Rat - Category: NA | 18,000.00, Rabbit - Category: NA | 58.60, Rat - Category: NA | No data available | No data available |
| 1-Methoxy-2-propanol - (107-98-2) | 5,000.00, Rat - Category: 5 | 13,000.00, Rabbit - Category: NA | No data available | No data available | No data available |
| Isopropyl Alcohol - (67-63-0) | 4,710.00, Rat - Category: 5 | 12,800.00, Rat - Category: NA | 72.60, Rat - Category: NA | No data available | No data available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA | No data available |
| Rosin, Fumeric - (800680-57-9) | No data available | No data available | No data available | No data available | No data available |
| Ethanol - (64-17-5) | 7,060.00, Rat - Category: NA | 20,000.00, Rabbit - Category: NA | 124.70, Rat - Category: NA | No data available | No data available |

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

| | | | | | |
|---|-------------------------------|----------------------------------|----------------------------------|-------------------|-------------------|
| Acetic acid, 1-methylethyl ester - (108-21-4) | 6,750.00, Rat - Category: NA | 20,000.00, Rabbit - Category: NA | 17,129.60, Rabbit - Category: NA | No data available | No data available |
| Cellulose Nitrate - (9004-70-0) | 5,000.00, Mouse - Category: 5 | No data available | No data available | No data available | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description |
|-------------------------------|----------|------------------------------------|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | --- | Not Applicable |
| Serious eye damage/irritation | 2 | Causes serious eye irritation. |
| Respiratory sensitization | --- | Not Applicable |
| Skin sensitization | --- | Not Applicable |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | --- | Not Applicable |
| Reproductive toxicity | --- | Not Applicable |
| STOT-single exposure | 3 | May cause drowsiness or dizziness. |
| STOT-repeated exposure | --- | Not Applicable |
| Aspiration hazard | --- | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|-----------------------|----------------------------|---|
| N-Butyl Acetate - (123-86-4) 18.00, Pimephales | promelas | 32.00, Artemia salina | 674.70 (72 hr), Scenedesmus subspicatus |
| Ethyl acetate - (141-78-6) 100.00, Danio rerio 100.00, Daphnia magna 100.00 (72 hr), | | Desmodesmus | subspicatus |
| 1-Methoxy-2-propanol - (107-98-2) 1,000.00, Oncorhynchus | mykiss | 500.00, Daphnia magna | 1,000.00 (96 hr), Selenastrum capricornutum |
| Isopropyl Alcohol - (67-63-0) 1,400.00, Lepomis | macrochirus | 100.00, Daphnia magna | 100.00 (72 hr), Scenedesmus subspicatus |

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

| | | | |
|--|---------------|---------------------|---|
| Titanium dioxide - (13463-67-7) 1,000.00, Fundulus | heteroclitus | 5.50, Daphnia magna | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Rosin, Fumeric - (800680-57-9) | Not Available | Not Available | Not Available |
| Ethanol - (64-17-5) 42.00, Oncorhynchus | mykiss | 2.00, Daphnia magna | 17.921 (96 hr), Ulva pertusa |
| Acetic acid, 1-methylethyl ester - (108-21-4) | Not Available | Not Available | Not Available |
| Cellulose Nitrate - (9004-70-0) | Not Available | Not Available | 579.00 (96 hr), Pseudokirchneriella subcapitata |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|---|---|--|---|
| 14.1. UN number | UN1210 | UN1210 | UN1210 |
| 14.2. UN proper shipping name | Printing ink | Printing ink | Printing ink |
| 14.3. Transport hazard class(es) | DOT Hazard Class: 3 DOT Label: 3 | IMDG: 3 Sub Class: Not Applicable EmS: F-E, S-D | Air Class: 3 Packing Instruction: Cargo Only - 364, Passenger -353 |
| 14.4. Packing group | II | II | II |

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

14.5. Environmental hazards

IMDG Marine Pollutant: Yes

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All components of this material are either listed or exempt from listing on the TSCA Inventory.

NFPA Rankings:



WHMIS Classification B2 D2B



US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Ethyl acetate (5,000.00)

N-Butyl Acetate (5,000.00)

EPCRA 302 Extremely Hazardous :

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

Isopropyl Alcohol

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Sprinter Marking, Inc Safety Data Sheet
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

Proposition 65 - Female Repro Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):
(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

- 1-Methoxy-2-propanol
- Acetic acid, 1-methylethyl ester
- Cellulose Nitrate
- Ethanol
- Ethyl acetate
- Isopropyl Alcohol
- N-Butyl Acetate
- Titanium dioxide

Penn RTK Substances (>1%):

- 1-Methoxy-2-propanol
- Acetic acid, 1-methylethyl ester
- Cellulose Nitrate
- Ethanol
- Ethyl acetate
- Isopropyl Alcohol
- N-Butyl Acetate
- Titanium dioxide

| |
|------------------------------|
| 16. Other information |
|------------------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

***Sprinter Marking, Inc* Safety Data Sheet**
18504 Fluorescent Yellow Marking Fluid

SDS Revision Date: 03/03/2016

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

This product is RoHS and REACH compliant. It does not contain any of the RoHS listed substances. It does not contain any chemical from the candidate list of Substances of Very High Concern (SVHC), Annex XIV, or Annex XVII of Reach.

This information is based on our present knowledge. However, it does not constitute a guarantee for any specific product properties.

Sprinter Marking urges the recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. The use of this product is beyond the control Sprinter Marking or it's distributor, therefore, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.

End of Document